| File E28476 | Vol. 4 * | Sec. 9 | Page 1 | 1978-05-19 2003-02-12 |
|-------------|--------------------|------------------|--------|--------------------------|
| | Vol. 20 Vol. 39 | Sec. 6 Sec. 1 | | |
| | Vol. 47 | Sec. 3 | | |
| | and Rep | ort | | |

DESCRIPTION

PRODUCT COVERED:

Component Connectors - Economy Interconnection (E.I.) System.

GENERAL:

These devices are multipole connectors with crimp terminals intended for connection of single conductors for use with printed wiring boards.

ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE USE):

Use - For use only in complete equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Conditions of Acceptability - In order to be judged acceptable as a component of electrical equipment, the following conditions should be met.

- 1. These devices should be used only where they will not interrupt the current.
 - 2. These devices have not been tested for current-carrying capability.
 - The suitability of the mounting means shall be judged in the end-

f these devices within the appliance enclosure should be seemed to between the live parts and the appliance are suitable for the particular application.

| File E28476 | Vol. 4 | Sec. 9 | Page 1A | | 1978-05-19 |
|-------------|----------|--------|---------|----------|------------|
| | * | | | Revised: | 2003-02-12 |
| | Vol. 20 | Sec. 6 | | | |
| | Vol. 39 | Sec. 1 | | | |
| | Vol. 47 | Sec. 3 | | | |
| | and Repo | ort | | | |

- 5. The adjacent poles may carry currents at potentials not exceeding 250 V between any two circuits provided with a min spacing of 3/64 in. Voltages in excess of 250 V but not exceeding 600 V may be considered where the spacings between adjacent live circuits or a live circuit and dead metal is a min of 1/8 in.
- 6. The electrical and mechanical contact between the receptacle and the printed wiring board is to be judged.
- 7. The suitability of the insulating materials used in the molded bodies shall be judged in the end-use equipment.
- 8. The operating temperature of these devices should not exceed the temperature ratings of the insulating materials. These materials may be used interchangeably at a max temperature of 65°C .

| File E28476 | Vol. 4 | Sec. 9 | Page 2A | 1978-05-19 2003-02-12 |
|-------------|----------|--------|---------|------------------------------|
| | Vol. 20 | Sec. 6 | | |
| | Vol. 39 | Sec. 1 | | |
| | Vol. 47 | Sec. 3 | | |
| | and Repo | ort | | |

Index to Illustrations - The following is a breakdown of the cat. nos. covered by this Report. They can be found in the illustrations noted below.

| Cat. No. | | | Ill. No. |
|-----------------|---------|---------|----------|
| 171822 | | | 1 and 7 |
| 171825 | | | 2 |
| 172732, 172800 | | | 2A |
| 173051 | | | 2B |
| 171826 | | | 3 |
| 170262 | | | 4 |
| 170263 | | | 5 |
| 170204, 170205, | 722560, | 722561 | 7 |
| 171880 | | | 8 |
| 170354, 170355, | | 170370, | 9 |
| 2106, | 172107 | | 10 |
| 171886, 171887 | | | 11 |

| *File E28476 | Vol. 4 | Sec. 9 | Page 2B | Issued: | 1978-05-19 |
|--------------|----------|--------|---------|----------|------------|
| | Vol. 20 | Sec. 6 | | Revised: | 2003-08-25 |
| | Vol. 39 | Sec. 1 | | | |
| | Vol. 47 | Sec. 3 | | | |
| | and Repo | rt | | | |

| Cat. No. | Ill. No |
|--|---------|
| 170376, 170377, 170429 170430, 172211, 172212 | 12 |
| 172213, 172214 | 13 |
| 172013 | 14 |
| 171825, 171826, 172051 through 172054 172057, 172058, 723860, 724024, 724031 | 15 |
| 172185 through 172188 | 16 |
| 172486 | 17 |
| 172487 | 18 |
| 172613 | 19 |
| 173936 | 20 |
| 173081 | 21 |
| 84000 | 22 |
| 84201 | 23 |