

NOTES:

- 1. OPERATING TEMPERATURE RANGE -55° C TO +125° C.
- 2. GOLD PLATED CASE AND LEAD.
- 3. EPOXY SEALED ON OPPOSITE END FROM GLASS SEAL.
- 4. PROPER INSTALLATION REQUIRES FIRM, STEADY PRESSURE UNTIL FLANGE IS FULLY SEATED.
- 5. RECOMMENDED MOUNTING HOLE: .128/.129 [3.25/3.28] DIA.
- 6. END OF LEAD INDICATED TO BE FREE OF BURRS.
- 7. TUSONIX STANDARD PART NUMBER: 4306-008.
 TUSONIX RoHS COMPLIANT PART NUMBER: 4306-008 LF.
 CUSTOMER MUST SPECIFY STANDARD OR RoHS PART NUMBER WHEN ORDERING.
- 8. RoHS COMPLIANT PART MARKED WITH ADDITIONAL GREEN DOT FOR IDENTIFICATION.

Ι.															
	Cx (pF)		TOL.	DC WORKING VOLTAGE		DC CURRENT	I.R.	D.W.V.	MIN. NO LOAD INSERTION LOSS (dB) @ 25° C PER MIL-STD-220					COLOR	
				85°C	125°C	(AMPS)	MIN.		1 MHz	10 MHz	100 MHz	1GHz	10 GHz	CODE	
	1000		+100% -0%	300	200	5	10 GΩ	500 VDC		5	20	35	45	GRAY	
REVISION RECORD	01 0	-							TOLERANCES Unless Otherwise Specified		Title	PRESS-IN EMI FILTER			
	9								DECIMAL ± / //		_/	LIMITICIEN			
Z Z	al Release 20060905-6-01								ANGLES ± ///		_/ Drawn	S.M. 09	-06-06	Scale 7 X	
VISIC	Rele 2006								TUSONIX		Approved T.C. 09-06-06				
Ŗ	Original C.O.							TUDUMIA TUCSON, ARIZONA		- _		4306-0	800		